

Making Your Job More Enjoyable



Compatible with Hi VALUE App

A2L
COMPATIBLE

VRM-2S VRM-2SV

Smart Digital Manifold Gauge

NEW



Smart and Precise

Smart and Wireless

- Work with Hi VALUE App
- Bluetooth connections with temp clamps & micron gauge (sold separately)

Aluminum Body w/ 1/4 Turn Ball Valve

- Reliable, efficient and durable
- Better work experience

Multi-Operation Modes

- Manifold mode with SH/SC display
- Pressure Test mode
- Evacuation mode

Folding Hook

- Hidden hook design
- Easy to transport

Digital and Accurate

- Class 0.4 accuracy with digital display
- Precision at a glance

Impact-Resistant

- Impact-resistant design
- Durable rubber cover

Model	VRM-2S	VRM-2SV
Refrigerant Type	R-11, R-12, R-13, R-22, R-23, R-32, R-113, R-114, R-115, R-116, R-123, R-124, R-125, R134A, R-236fa, R-245fa, R-290, R401A, R-401B, R-402A, R-402B, R-403B, R-404A, R-406A, R-407A, R-407B, R-407C, R-408A, R-409A, R-410A, R-413A, R-414A, R-414B, R-416A, R-417A, R-417C, R-420A, R-421A, R-421B, R-422A, R-422B, R-422C, R-422D, R-424A, R-427A, R-428A, R434A, R-437A, R-438A, R-448A, R-449A, R-450A, R-452A, R-452B, R-453A, R-454B, R-458A, R-500, R-501, R-502, R-503, R507A, R-508B, R-513A, R-600, R-600a, R-601, R-601a, R-744*, R-1233zd, R-1234yf, R-1234ze Firmware can be updated at VALUE website or with Hi VALUE App *Maximum pressure: 725 Psi (5000 kPa)	
Pressure Range	-30 inHg to 725 psi	
Bluetooth Range	80 m line of sight	
Power Supply	Rechargeable Li-Ion Battery	
Accessory	Bluetooth Temperature Clamps VMT-1S (Low Side), VMT-2S (High Side), Charging Cable, Carry Case	VMV1S Micron Gauge in addition to the VRM-2S Kit